

Republic of the Philippines

			23dBm@ 48Mbps 22dBm@ 54Mbps Horizontal beamwidth(H): 43° Vertical beamwidth(V): 41° Memory: 32MBSDRAM 8MBFLASH Processor: Athlon MIPS 24K, 400MHz Power supply: 24V / 0.5A (power adapter included) Operation temp -30°C... 75°C Permissible relative humidity: 5%... 95% Weight: 0.3kg Dimensions: 278 x 80 x 59mm		
3	4	Sets	Point to Point, Litebeam 5GHz Litebeam VLAN Capable	400000	1600000
4	1	Unit	Sound System Cable and Jack and Accessories 3pcs - USB 7.1 Sound Card with 3.5mm stereo and mic sound card splitter 3pcs - Audio Cable 3.5mm to Dual 6.35mm Male Mini Plug 3 meters 3pcs - Audio Cable 3.5mm to Dual 6.35mm Male Mini Plug 5 meters 3pcs - 3.5mm male audio jack to RCA male cable, 3 meters 3pcs - 3.5mm male audio jack to RCA male cable, 5 meters 1pc - 3pin XLR female jack to dual 2 male plug Y splitter adapter cable wire, 30cm 1pc - 3.5mm stereo jack to XLR 3pin male Y splitter cable, 3 meters Type C Sound Card Splitter HDMI Video Capture USB 3.0	600002	600002
5	6	Pcs	RAM DDR3, 8GB, DIMM, 1600MHz	200000	1200000
6	7	Pcs	RAM DDR4, 8GB, DIMM, 2666MHz	300000	2100000

2 Delivery Period ____ calendar days from the receipt of P.O

- 3 Price quotations must be valid for a period of sixty (60) calendar days from date of submission and shall include all taxes, duties and/or levies payable. Bidders shall also indicate the brand and model of the items being offered**
- 4 Warranty shall be for a period of six (6) months for supplies and materials. Warranty for equipment must not be less than six (6) months from date of acceptance and shall be**

6 The CVSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/informalities therein and to accept such bids it may consider as most